

Collections: FOREST

ADLUX

FC-50

Product ID	Dimensions, mm (H x W x D)	Color temperature, Tc [K]	Finish	Input voltage	Power consumption, W	IP	Dimming ready*
FC50-DW-O	200 -2500 x 500 x 48	3800-4200 ●	Oak	100-240VAC 50/60 Hz	9	20	Yes
FC50-DW-WO	200 -2500 x 500 x 48	3800-4200 ●	White oak	100-240VAC 50/60 Hz	9	20	Yes
FC50-DW-W	200 -2500 x 500 x 48	3800-4200 ●	Walnut	100-240VAC 50/60 Hz	9	20	Yes
FC50-DW-A	200 -2500 x 500 x 48	3800-4200 ●	Ash	100-240VAC 50/60 Hz	9	20	Yes
FC50-DW-C	200 -2500 x 500 x 48	3800-4200 ●	Cherry	100-240VAC 50/60 Hz	9	20	Yes
FC50-DW-E	200 -2500 x 500 x 48	3800-4200 ●	Exclusive	100-240VAC 50/60 Hz	9	20	Yes
FC50-WW-O	200 -2500 x 500 x 48	2900-3100 ●	Oak	100-240VAC 50/60 Hz	9	20	Yes
FC50-WW-WO	200 -2500 x 500 x 48	2900-3100 ●	White oak	100-240VAC 50/60 Hz	9	20	Yes
FC50-WW-W	200 -2500 x 500 x 48	2900-3100 ●	Walnut	100-240VAC 50/60 Hz	9	20	Yes
FC50-WW-A	200 -2500 x 500 x 48	2900-3100 ●	Ash	100-240VAC 50/60 Hz	9	20	Yes
FC50-WW-C	200 -2500 x 500 x 48	2900-3100 ●	Cherry	100-240VAC 50/60 Hz	9	20	Yes
FC50-WW-E	200 -2500 x 500 x 48	2900-3100 ●	Exclusive	100-240VAC 50/60 Hz	9	20	Yes

* Optional

