

Collections: FOREST

ADLUX

FW-30

Product ID	Dimensions, mm (H x W x D)	Color temperature, Tc [K]	Finish	Input voltage	Power consumption, W	IP	Dimming ready*
FW30-DW-O	100 x 300 x 68	3800-4200 ●	Oak	100-240VAC 50/60 Hz	7	20	No
FW30-DW-WO	100 x 300 x 68	3800-4200 ●	White oak	100-240VAC 50/60 Hz	7	20	No
FW30-DW-W	100 x 300 x 68	3800-4200 ●	Walnut	100-240VAC 50/60 Hz	7	20	No
FW30-DW-A	100 x 300 x 68	3800-4200 ●	Ash	100-240VAC 50/60 Hz	7	20	No
FW30-DW-C	100 x 300 x 68	3800-4200 ●	Cherry	100-240VAC 50/60 Hz	7	20	No
FW30-DW-E	100 x 300 x 68	3800-4200 ●	Exclusive	100-240VAC 50/60 Hz	7	20	No
FW30-WW-O	100 x 300 x 68	2900-3100 ●	Oak	100-240VAC 50/60 Hz	7	20	No
FW30-WW-WO	100 x 300 x 68	2900-3100 ●	White oak	100-240VAC 50/60 Hz	7	20	No
FW30-WW-W	100 x 300 x 68	2900-3100 ●	Walnut	100-240VAC 50/60 Hz	7	20	No
FW30-WW-A	100 x 300 x 68	2900-3100 ●	Ash	100-240VAC 50/60 Hz	7	20	No
FW30-WW-C	100 x 300 x 68	2900-3100 ●	Cherry	100-240VAC 50/60 Hz	7	20	No
FW30-WW-E	100 x 300 x 68	2900-3100 ●	Exclusive	100-240VAC 50/60 Hz	7	20	No

* Optional

